



FLOOR SHINE

BRILLIANT GLOSS ACRYLIC POLYMER POLISH

Excellent floor polish formulation

ActiveEco Floor Shine is a non-hazardous, new generation floor finish with that provides optimal durability and resistance to traffic, black heel marks and scuffing. It is easy to apply and dries to a brilliant gloss, making it the ideal polish for various establishments, workplaces, retail shops, and homes.

ActiveEco Floor Shine eliminates the need for a base sealer due to its exceptional leveling properties. Its high solids content builds quickly, thus, fewer coats are required to achieve flawless gloss and protection.

Benefits

- Dries to a brilliant wet-look gloss from the very first application of two or more coats.
- Responds remarkably well to cleaning and buffing.
- Protects wooden floors from traffic, black heel marks and scuffing.
- Maintains exceptional non-slip properties.
- Enhances the natural beauty of wood floors by providing a durable protective coating.
- Can be used with electric buffing machines.

FLOOR SHINE

BRILLIANT GLOSS ACRYLIC POLYMER POLISH

Recommended Applications

Ideal for use on:

- Vinyl
- Slate
- Granite
- Terrazzo
- Terracotta
- Linoleum
- Wood
- Marble

Use a base coat first before applying on stone surfaces or polished concrete.



Application

- Use a clean polish applicator to apply **ActiveEco Floor Shine**. Using slightly overlapping strokes, apply a thin coat over the floor area.
- Allow to dry (30 to 40 minutes).
- Apply 3 to 5 coats of **ActiveEco Floor Shine** depending on the porosity of the surface and the expected amount of traffic.
- Repeated thin, evenly-spread coats are better than one heavy application.
- If a base coat has been applied, only 2 to 3 coats of **ActiveEco Floor Shine** can be applied as soon as the base coat is dry to the touch.
- Coverage is 50-80m² per litre per coat depending on the porosity of the surface.

Part No #	Description	Size
AEFS-5	ActiveEco Floor Shine	5 Litre
AEFS-15	ActiveEco Floor Shine	15 Litre